# **BUILDING PRODUCT INFORMATION SHEET**

## **NZTP** Interior Mouldings

This document has been produced in compliance with the requirements of the Building (Building Product Information Requirements) Regulations 2022.

#### **Product:**

NZ Timber Profiles Itd catalogue range of Interior Mouldings.

#### **COMPONENTS** –

New Zealand Radiata Pine (pinus radiata), as untreated, kiln-dried timber. Other timber species as per special order.

All NZTP fingerjoint pine is supplied as FSC Mix 70% (FSC-Cert: SGSHK-COC-510017). All NZTP fingerjoint pine is grown and milled in New Zealand.

USE - Suitable for interior use only.

#### **Manufacturer Details:**

NAME - NZ Timber Profiles Limited

PHYSICAL ADDRESS – 45-51 Tironui Road, Papakura, Auckland

WEBSITE - www.nztimberprofiles.co.nz

**EMAIL** – sales@nztimberprofiles.co.nz

NZBN - 9429031466462

### **Relevant Building Code Obligations:**

**CLAUSE B2 – DURABILITY** 

B2.3.1 (c) – Interior use only. Dried to less than 16% moisture. Treatment not required as per NZ3602:2003.

#### **Limitations of Use:**

Not suitable for exterior use. Not suitable for areas with excessive moisture exposure, such as showers.

### **Installation & Maintenance Requirements:**

Interior mouldings should be sealed on all sides to prevent the ingress of moisture. Oil-based or solvent-based timber primer is the best-practice solution. Exposed surfaces should be regularly painted with an acrylic or enamel paint suitable for interior timber, to maintain a 5-year durability in accordance with AS/NZS 2311.

